

Effect of nickel electroplating process time variation over aluminum on crystalplane orientation

by Cahaya Rosyidan FTKE

Submission date: 31-Mar-2024 01:27AM (UTC+0700)

Submission ID: 2207546240

File name: 34._Cahaya_Rosyidan.pdf (524.46K)

Word count: 3911

Character count: 20695

RESEARCH ARTICLE | JUNE 12 2023

Effect of nickel electroplating process time variation over aluminum on crystalplane orientation FREE

Cahaya Rosyidan ✉; Bambang Soegijono; Budhy Kurniawan



AIP Conference Proceedings 2598, 040009 (2023)

<https://doi.org/10.1063/5.0126191>



View
Online



Export
Citation

CrossMark

Downloaded from http://pubs.aip.org/aip/acp/article-pdf/doi/10.1063/5.0126191/17995308/040009_1_5.0126191.pdf

AIP Advances

Why Publish With Us?



25 DAYS
average time
to 1st decision



740+ DOWNLOADS
average per article



INCLUSIVE
scope

[Learn More](#)

Effect Of Nickel Electroplating Process Time Variation Over Aluminum On CrystalPlane Orientation

Cahaya Rosyidan,^{1,2, c}, Bambang Soegijono^{1,b}, and Budhy Kurniawan^{1,a}

¹Departement of Physics, Universitas Indonesia, Depok 16424, Indonesia

²Teknik Perminyakan, Fakultas Teknologi Kebumihan dan Energi, Universitas Trisakti, Gedung D, Kampus A, Jl. Kyai Tapa no.1, Jakarta, Indonesia.

Corresponding author: ^{a)} budhy.kurniawan@sci.ui.ac.id
^{b)} bambangsg11@yahoo.com
^{c)} cahaya.rosyidan@ui.ac.id

Abstract. Metal plating starts to be widely used as a way to prevent metal corrosion. Apart from preventing corrosion, metal coatings were being developed to thicken the metal, increase its hardness, wear resistance and corrosion resistance. The purpose of this research is to make Ni coating over Al substrate in time variation differences (3.5 h, 4.5 h and 5 h) with a constant current of 50 mA cm⁻². The characterization of the materials used was from SEM-EDS, XRD and digital cameras. The SEM characterization results showed a crystal shape similar to a pyramid and contained Ni oxide content in the Ni coating, although in the XRD observations did not appear. The increasing of the coating time will increase the crystal size in the direction of the preferred plane orientation [111] which was confirmed by the calculation of the orientation index. The Ni 5 sample has hydrophobic properties with a contact angle of 91 °.

Keywords: electrodeposition, hydrophobic, SEM

INTRODUCTION

Aluminum metal is one of the materials that is widely used by people such as transportation, buildings and construction as well as home accessories and decorations because of its soft and stylish appearance, its color is silvery and shiny. Prices are quite affordable and easy to obtain, different uses of aluminum metal in the engineering field. The use of aluminum metal in the engineering field is easy to form, a good heat conductor, resistant to cold temperatures, and aluminum can also be corroded. [1], [2]

Metal plating is starting to be widely used as a way to prevent metal from corrosion. In addition to preventing corrosion, metal coatings have been developed to thicken the metal, increase its hardness, wear resistance and corrosion resistance. [3] - [6]. Many factors affect to get this benefits results which are the composition of the material, the composition of the solution [7], [8], the temperature of the solution [9] - [12], the current density of the solution [13] - [15], the duration of immersion and the electric voltage [5], [13] - [20]. The electroplating process has long been recognized for plating metals such as nickel, chrome, gold and silver. Electroplating method offers many advantages such as faster, reliable and relatively cheaper [21] [22] [23] - [26].

The crystal size has a direct impression on the surface energy of the coating. Along with surface energy, surface morphology also plays a vital role in surface wettability. Because of the change in current density (j), thickness, layer morphology and crystal size can be obtained. Therefore, this research will look for changes in the microstructure of the layer and the distribution of Ni particles on the Al substrate with time variations [27], [28].

Research conducted by Zubar yo et al using electrolyte solutions of NiSO₄·6H₂O (210 g L⁻¹), NiCl₂·6H₂O (20 g L⁻¹) and H₃BO₃ (45 g L⁻¹) [29]. This solution is also called a watts solution because it uses three main supporting components: nickel sulfate, nickel chloride, and boric acid.

Although research on Nickel plating on aluminum substrates has been done a lot. Eventhough many studies of nickel-to-aluminum plating with time variations have been carried out, there are still many lack of details regarding the effect of nickel plating on aluminum by the electrodeposition method on crystal size, surface morphology, statisticalcrystal distribution and wettability. Material characterization in this study using SEM, XRD and digital cameras.

METHOD

The anode rod used is 98% pure nickel metal **Table 2** and the cathode is an aluminum substrate **Table 1**. The electrolyte solution used was a watts solution of $\text{NiSO}_4 \cdot 6\text{H}_2\text{O}$ (210 g L^{-1}), $\text{NiCl}_2 \cdot 6\text{H}_2\text{O}$ (20 g L^{-1}) and H_3BO_3 (45 g L^{-1}) with quality / grade analyst from the chemical manufacturer Merck. Before the experiment, the aluminum metal was polished and washed in an ultrasonic bath. The watts solution to be used is treated first by stirring for 1 hour with a magnetic stirred (Bante Instrument MS 3000) at a speed of 200 rpm to get homogeneity. The electroplating experiment used a current of 50 mA cm^{-2} with a time variation of 3.5 hours, 4.5 hours and 5 hours.

TABLE 1. Chemical composition of the Al alloy substrates (wt%), determined from the X-ray fluorescence measurement

Element	Al	Mg	Fe
Concentration	96,88	1,49	1,63

Each sample will be written as Ni 3.5, Ni 4.5 and Ni 5 to represent each experiment with time variation in this study. The anode rod used in this research has the following composition:

TABLE 2. Chemical composition of the pure Ni (wt%), determined from the X-ray fluorescence measurement.

Element	Concentration (%)
Al (Alumunium)	0,02
Ca (Kalsium)	0,04
Fe (Besi)	0,23
Ni (Nikel)	98,01
Y (Yttrium)	1,61
Zr (Zirkon)	0,04
Nb (Niobium)	0,05

Surface morphological analysis of the nickel plating experiment on aluminum using FE-SEM (FE-SEMFEI INSPECT F50 EDAX EDS Analyzer) with magnifications of $2500\times$ and $10000\times$. The crystalline structure of the Nickel layer was identified by XRD (Rigaku RINT 2000 with Cu K radiation). XRD data is processed with the help of HighScore Plus software to refined and calculate the crystal size, besides that, the position of the particles can also be known.

Water contact angle observations were taken using a Canon 1000D EOS camera. The value determines criteria of the angle θ as $\theta < 90^\circ$, $90^\circ \leq \theta < 150^\circ$, $150^\circ \leq \theta < 180^\circ$ for being hydrophilic, hydrophobic, and superhydrophobic, respectively [28]

RESULT AND DISCUSSION

Electroplating is used to form a microstructural pattern of nickel plating over aluminum. The time variation will provide information about changes in the shape of the surface morphology and affect the size of the crystals (3.5 h, 4.5 and 5). In addition, we can determine the crystal size distribution using statistical analysis with ImageJ (Open Access) and Origin (OriginLab Corporation). By measuring the length of the grain diameter by ImageJ, then processing it by Origin.

Figure 1 shows the microstructure evolution of pure Nickel plating over aluminum with time variations. It can be seen from the SEM results that Nickel is evenly distributed over the Aluminum substrate in the electroplating process with a time of 3.5 h (**Figure 1a**). Then it can be seen visually from the increase in time to 4.5 h the crystal size is getting bigger and looks quite close to each other (**Figure 1b**). A customarily distributed Gaussian pattern can confirm this. Finally, at the time variation of 5 h, the crystals became visually more compact and bonded to one another (**Figure 1c**).

As additional information, it can be seen that all layers of Ni 3.5 - Ni 5 (**Figure. 1 a - c**), showed a half pyramidal structure with a crystal (8 - 30 μm) [30]. This pyramidal structure is morphologically typical for Ni plating with a preferred plane texture in a plane. [100,111] [31] - [33].




FIGURE 1 (a-c). SEM micrographs for different layers show the morphology of pure Ni coating separately deposited and distribution particle obtained using ImageJ combine Origin with corresponding Gauss fitting function

In the electroplating process, an anodizing event occurs. The cathode attracts the positive ions because a unidirectional electric current flows between the two electrodes in the electrolyte solution. Apart from releasing positive ions, the anode electrode also releases oxygen. Oxygen gas needs to be considered because as an inhibitor for anode electrode to releases positive ions [34], [35].

The presence of oxygen gas can be seen with the EDS pattern of nickel electroplating on an aluminum substrate presented in **Figure 2**. EDS analyzes the presence of significant peaks of nickel and oxygen peaks.

Transferring positive ions from the anode to the cathode causes a small amount of carbon to accumulate in the Ni anode rod. Readings of how much the weight percent Ni, C and O2 can be seen in table 3.




FIGURE 2. EDS pattern showing an element of Ni, C and O at various times

TABLE 3. Ni, C and O content on electrodeposit Ni Film with different time

Sampel	Ni (wt%)	C (wt%)	O (wt%)
Ni 3.5	98.30	0.90	0.80
Ni 4.5	96.86	2.00	1.14
Ni 5	95.47	2.41	2.12

When viewed from the data in table 3, it can be seen that the Ni 3.5 sample weight percent Ni 98.30 (wt%), C 0.90 (wt%) and O2 0.80 (wt%). Then for the sample Ni 5 has a weight percent Ni 95.47 (wt%), C 2.00 (wt%) and O2 1.14 (wt%). It can conclude that the increasing variety of time will increase the weight percent (wt%) of O2. the increase in O2 comes from oxidized Ni, but even though EDS detected O2, it was not observed by XRD

The calculation of the μ orientation index aims to determine the crystal structure growing or even shrinking along with the electroplating process with time variations. The orientation index $\mu(hkl)$ is calculated using the equation:

$$\mu(hkl) = \frac{I(hkl)/I_0(hkl)}{\sum_n I(hkl)/I_0(hkl)}$$

Where $I(hkl)$ is the peak intensity of each crystal plane from the research data, while $I_0(hkl)$ is the peak intensity of the crystals obtained from the ICSD (Inorganic Crystal Structure Database). In addition, $\sum I(hkl)$ is the summation of the three peak intensities from the research data and $\sum I_0(hkl)$ is the summation of the three peak intensities from the ICSD data. An index value greater than 1 [$\mu(hkl) \geq 1$] indicates that the crystal field (hkl) is growing, meanwhile, if [$\mu(hkl) \leq 1$] indicates that the crystal field is shrinking.

TABLE 4. Calculation of automatic index for coating Ni over Al with time variation


sample	hkl			$\mu(hkl)$		
	[111]	[002]	[022]	[111]	[002]	[022]
Ni 3.5	3702	1950	668	0,70	1,18	1,08
Ni 4.5	8570	967	619	1,63	0,58	1,00
Ni 5	3466	2006	557	0,66	1,22	0,90

In this study, the Ni over Al coating with the current density was kept constant at 50 mA cm^{-2} with time variations showing that the crystal plane grew and shrank from the calculation of the orientation index μ . In the sample Ni 4.5, the crystal plane [111] known to have a value of 1.63, which means that compared to Ni 3.5, the crystal plane grows more due to the addition of time. Crystal field [022] experienced growth in the Ni 3.5 and Ni 5 samples, but shrank in the Ni 5 samples. This is due to a decrease in electrical conductivity from the use of solution concentration..

The time variation effect affects the growth orientation of a particular crystal plane. The longer the plating time will affect the orientation of a certain crystal plane. This is estimated from the higher concentration of Ni^{2+} ions in solution. The growth of plane orientation [111] has advantages including anti-corrosion, increasing electrical conductivity and increasing mechanical properties [36].

The results of the plane orientation in table 4 are confirmed by the XRD pattern produced. The XRD pattern is shown in **Figure 3** results from the linear refinement of the XRD pattern processed using the HighscorePlus Software. The crystal structure formed is a **face centered cubic (FCC)** which shows **three significant peaks for the plane [111], [002] and [022]**. The phase formed is a single phase and no other phases are formed on the surface of the Ni layer. The results of XRD data processing did not show nickel oxide, even though O_2 was detected by EDS (**Figure 2**), because the oxide formed in Ni was small.

There are three significantly different peak intensities, the peaks are the plane [111], [002] and [022]. The difference in peak intensity is due to the difference in mass density on the surface of each crystal plane due to time variations.

**FIGURE 3.** XRD pattern of electrodeposit Ni onto Al substrate with various time at constant current densities 50 mA cm^{-2}

The calculation of crystal size uses the Debye-Scherrer equation, where k is a constant of 0.9, β (the width of the diffraction peak of FWHM in radians), λ (the x-ray wavelength using $\text{Cu K}\alpha$ radiation is 0.154 nm), and θ (Bragg's angle) [37].

$$D = \frac{k}{\beta \cos \theta}$$

The crystal parameters of the sample after doing Rietvel Refinement using HighScore Plus software are presented in table 5. Rietveld corrections were made until the GOF (Goodness of fit) value was less than 2.5% and the ROP

(R-weighted pattern) value was less than 10%. The atom's position can also be seen in the table which states that the atom's position occupies every point in the cube with its occupancy value of 1, so it can be concluded that there is no atomic shift.

TABLE 5. Crystal parameter of Ni films at various times and constant current densities at 50mA cm⁻²

Parameter	Sample		
	Ni 3.5	Ni 4.5	Ni 5
Crystal structure	Cubic	Cubic	Cubic
Space Group	FCC	FCC	FCC
space Group Number	Fm-3m	Fm-3m	Fm-3m
Lattice constan (Å)a = b = c	225	225	225
Volume (Å ³)	3,5175	3,5206	3,5152
Densitas (g/cm ³)	8,79	8,88	8,79
d-spacing (Å)	1,0142	1,0093	2,04906
Crystallite Size Debye-Scherrer(nm)	24	42	23
Atomic Position	X	0	0
	Y	0	0
	Z	0	0
Occupancy	1	1	1
R-weighted pattern GOF (Goodness of Fit)	7,67075	9,09029	7,249
	0,74151	1,00618	1,986

Determination of hydrophilic and hydrophobic properties can be done using a water drop test over the sample. **Figure 4** presents a photo of the results of the drop test that has been carried out. In the drop test, it can be seen that there is a difference in contact angle due to time variations. Therefore, it can be concluded that over time the angle of contact increases as well. This has also been observed by [38] in their study. Samples Ni 3.5 and Ni 4.5 show hydrophilic properties because the contact angle is 73 ° and 88 °. Ni 5 sample has hydrophobic properties because it has a contactangle of 91 ° where the range for hydrophobic properties ($90^{\circ} \leq \theta < 150^{\circ}$) [38].




Figure 4: Wettability of the various Ni films deposited on the Al alloy substrates at different time.

CONCLUSION AND RECOMMENDATION

Nickel plating has been successfully carried out on the Al substrate with time variations. The effect of Ni coating affects surface morphology, crystal orientation, crystallite size and wettability. The Ni 4.5 sample has the largest crystal size of 44nm with the most dominant crystal plane [111] this is also confirmed by calculating the orientation index, this means that Ni elektropalting on aluminium with time variations has been successfully carried out. The morphological structure of the crystal is in the form of a pyramid completely distributed over the Al substrate as seen from the Gaussian plot. In the Ni 5 sample has hydrophobic properties with a contact angle of 91°. Even though the EDS characterization contained Ni oxide, but in XRD observations were not found because the O₂ that formed was very small

REFERENCES

- [1] J. Sudagar, J. Lian, and W. Sha, "Electroless nickel, alloy, composite and nano coatings - A critical review," *J. Alloys Compd.*, vol. 571, pp. 183–204, 2013.
- [2] A. V. Logunov, D. V. Danilov, and R. V. Khramin, "High-Strength Nickel-Based Alloy SLGS-5 for Operation in Active Marine Salt Corrosion Environment," *Mater. Today Proc.*, vol. 11, pp. 453–458, 2019.
- [3] N. Li, W. Li, X. Yang, Y. Xu, and A. Vairis, "Corrosion characteristics and wear performance of cold sprayed coatings of reinforced Al deposited onto friction stir welded AA2024-T3 joints," *Surf. Coatings Technol.*, vol. 349, no. April, pp. 1069–1076, 2018.
- [4] F. Soleimangoli, S. A. Hosseini, A. Davoodi, A. Mokhtari, and M. Alishahi, "Effect of NH₄Cl on the microstructure, wettability and corrosion behavior of electrodeposited Ni–Zn coatings with hierarchical nano/microstructure," *Surf. Coatings Technol.*, vol. 394, no. April, p. 125825, 2020.
- [5] B. ABEDINI, N. PARVINI AHMADI, S. YAZDANI, and L. MAGAGNIN, "Electrodeposition and corrosion behavior of Zn–Ni–Mn alloy coatings deposited from alkaline solution," *Trans. Nonferrous Met. Soc. China* (English Ed.), vol. 30, no. 2, pp. 548–558, 2020.
- [6] K. S. Jyothender, A. Gupta, and C. Srivastava, "Grain boundary engineering in Ni-carbon nanotube composite coatings and its effect on the corrosion behaviour of the coatings," *Materialia*, vol. 9, no. October 2019, p. 100617, 2020.
- [7] B. Soegijono, F. B. Susetyo, H. A. Notonegoro, and M. C. Fajrah, "Electrochemical Behavior, Structure, and Morphology of Electrodeposited Nickel on Copper Alloy Prepared from Sulfate Bath without Additive Addition," *FLYWHEEL J. Tek. Mesin Untirta*, vol. VI, no. 1, p. 6, 2020.
- [8] I. Kharmachi, L. Dhoubi, P. Berçot, and M. Rezaei, "Pulse plating as an alternative approach to improve Ni-Co alloys properties coated from a bath with a low nickel content," *J. Mater. Environ. Sci.*, vol. 7, no. 5, pp. 1670–1684, 2016.
- [9] K. Mausam and M. Goyal, "Development of nanocrystalline Ni-Al coatings and its thermal stability," *Mater. Today Proc.*, no. xxxx, 2020.
- [10] F. B. Susetyo, M. C. Fajrah, and B. Soegijono, "Effect of electrolyte temperature on properties of nickel film coated onto copper alloy fabricated by electroplating," *e-Journal Surf. Sci. Nanotechnol.*, vol. 18, no. 10, pp. 223–230, 2020.
- [11] P. P. Surabaya, "ANALISIS PENGARUH ELECTROPLATING PADA ALUMINIUM ALLOY 2024 MENGGUNAKAN NIKEL DAN KROM TERHADAP LAJU KOROSI," no. September, pp. 1–6, 2018.
- [12] L. Jinlong, L. Tongxiang, and W. Chen, "Effect of electrodeposition temperature on grain orientation and corrosion resistance of nanocrystalline pure nickel," *J. Solid State Chem.*, vol. 240, pp. 109–114, 2016.
- [13] B. Li et al., "Effect of current density and deposition time on microstructure and corrosion resistance of Ni-W/TiN nanocomposite coating," *Ceram. Int.*, vol. 45, no. 4, pp. 4870–4879, 2019.
- [14] H. S. Maharana, B. Bishoyi, and A. Basu, "Current density dependent microstructure and texture evolution and related effects on properties of electrodeposited Ni-Al coating," *J. Alloys Compd.*, vol. 787, pp. 483–494, 2019.
- [15] Sutomo, Senen, and Rahmat, "Pengaruh arus dan waktu pada pelapisan nikel dengan elektroplating untuk bentuk plat," *Fak. Tek. Univ. Diponegoro, Indones.*
- [16] S. Raharjo, "Pengaruh Variasi Tegangan Listrik Dan Waktu Proses Electroplating Terhadap Sifat Mekanis Dan Struktur Mikro Baja Karbon Rendah Dengan Krom Samsudi," *Jurnal.Unimus.Ac.Id*, pp. 296–308, 2010.
- [17] A. M. Koten, J. U. Jasron, J. T. Mesin, U. N. Cendana, and K. Mikro, "Pengaruh Variasi Tegangan dan Waktu Terhadap Kekerasan Lapisan Nikel dengan Metode Electroplating pada Coran Aluminium scrap," vol. 03, no. 01, 2016.
- [18] A. F. Alphanoda, "Pengaruh Jarak Anoda-Katoda dan Durasi Pelapisan Terhadap Laju Korosi pada Hasil

- Electroplating Hard Chrome," *J. Teknol. Rekayasa*, vol. 1, no. 1, p. 1, 2017.
- [19] D. Suwardi, "Pengaruh Elektroplating Nikel Dengan Variasi Waktu Pelapisan 30, 60, 90, 120, 150 Menit Terhadap Kekasaran Permukaan, Titik Luluh Kekuatan Tarik Maksimum Baja Karbon," *J. Tek. mesin Fak. Tek. Univ. MUHAMMADIYAH SURAKARTA*, 2017.
- [20] M. Y. Niam, H. Purwanto, and S. M. B. Respati, "Pengaruh Waktu Pelapisan Elektro ...," vol. 13, no. 1, pp. 7–10, 2017.
- [21] F. Nasirpour et al., "An investigation on the effect of surface morphology and crystalline texture on corrosion behavior, structural and magnetic properties of electrodeposited nanocrystalline nickel films," *Appl. Surf. Sci.*, 2014.
- [22] M. Abdulwahab, O. S. I. Fayomi, and A. P. I. Popoola, "Structural evolution, thermomechanical recrystallization and electrochemical corrosion properties of Ni-Cu-Mg amorphous coating on mild steel fabricated by dual-anode electrolytic processing," *Appl. Surf. Sci.*, 2016.
- [23] M. M. Kamel, Z. M. Anwer, I. T. Abdel-Salam, and I. S. Ibrahim, "Nickel electrodeposition from novel lactate bath," in *Transactions of the Institute of Metal Finishing*, 2010.
- [24] M. A. M. Ibrahim and R. M. Al Radadi, "Role of glycine as a complexing agent in nickel electrodeposition from acidic sulphate bath," *Int. J. Electrochem. Sci.*, 2015.
- [25] C. qun LI, X. hai LI, Z. xin WANG, and H. jun GUO, "Nickel electrodeposition from novel citrate bath," *Trans. Nonferrous Met. Soc. China (English Ed.)*, 2007.
- [26] Z. Shafiee, M. E. Bahrololoom, and B. Hashemi, "Electrodeposition of nanocrystalline Ni/Ni-Al₂O₃ nanocomposite modulated multilayer coatings," *Mater. Des.*, 2016.
- [27] M. H. M. Zaki, Y. Mohd, and N. N. C. Isa, "The effect of current density on surface properties of electrodeposited copper coatings on modified aluminium," in *AIP Conference Proceedings*, 2018.
- [28] A. Augustin, K. U. Bhat, K. R. Udupa, and A. C. Hegde, "Electron microscopic study of nodules formed during electrodeposition of copper on aluminium," in *Materials Science Forum*, 2015.
- [29] T. Zubar et al., "The effect of heat treatment on the microstructure and mechanical properties of 2d nanostructured au/nife system," *Nanomaterials*, vol. 10, no. 6, pp. 1–14, 2020.
- [30] S. Spanou, E. A. Pavlatou, and N. Spyrellis, "Ni/nano-TiO₂ composite electrodeposits: Textural and structural modifications," *Electrochim. Acta*, vol. 54, no. 9, pp. 2547–2555, 2009.
- [31] T. Lampke, B. Wielage, D. Dietrich, and A. Leopold, "Details of crystalline growth in co-deposited electroplated nickel films with hard (nano)particles," *Appl. Surf. Sci.*, vol. 253, no. 5, pp. 2399–2408, 2006.
- [32] S. Pathak et al., "Influence of lower current densities on the residual stress and structure of thick nickel electrodeposits," *Surf. Coatings Technol.*, vol. 205, no. 12, pp. 3651–3657, 2011.
- [33] S. A. Lajevardi, T. Shahrabi, J. A. Szpunar, A. Sabour Rouhaghdam, and S. Sanjabi, "Characterization of the microstructure and texture of functionally graded nickel-Al₂O₃ nano composite coating produced by pulse deposition," *Surf. Coatings Technol.*, vol. 232, pp. 851–859, 2013.
- [34] M. B. Radovanović and M. M. Antonijević, "Protection of copper surface in acidic chloride solution by non-toxic thiadiazole derivative," *J. Adhes. Sci. Technol.*, vol. 31, no. 4, pp. 369–387, 2017.
- [35] Z. Z. Tasic, M. M. Antonijević, M. B. Petrovic Mihajlovic, and M. B. Radovanovic, "The influence of synergistic effects of 5-methyl-1H-benzotriazole and potassium sorbate as well as 5-methyl-1H-benzotriazole and gelatin on the copper corrosion in sulphuric acid solution," *J. Mol. Liq.*, vol. 219, pp. 463–473, 2016.
- [36] R. SEAKR, "Microstructure and crystallographic characteristics of nanocrystalline copper prepared from acetate solutions by electrodeposition technique," *Trans. Nonferrous Met. Soc. China (English Ed.)*, vol. 27, no. 6, pp. 1423–1430, 2017.
- [37] W. D. Callister, "Materials science and engineering: An introduction (2nd edition)," *Mater. Des.*, vol. 12, no. 1, p. 59, 1991.
- [38] C. R. Thurber et al., "Electrodeposition of 70-30 Cu-Ni nanocomposite coatings for enhanced mechanical and corrosion properties," *Curr. Appl. Phys.*, vol. 16, no. 3, pp. 387–396, 2016.

Effect of nickel electroplating process time variation over aluminum on crystalplane orientation

ORIGINALITY REPORT

17%

SIMILARITY INDEX

15%

INTERNET SOURCES

3%

PUBLICATIONS

0%

STUDENT PAPERS

PRIMARY SOURCES

1

www.jstage.jst.go.jp

Internet Source

6%

2

jurnal.fmipa.unila.ac.id

Internet Source

6%

3

Arun Augustin, K. Rajendra Udupa, K. Udaya Bhat. "Effect of coating current density on the wettability of electrodeposited copper thin film on aluminum substrate", Perspectives in Science, 2016

Publication

1%

4

jurnal.untidar.ac.id

Internet Source

1%

5

Hari Karyadi Oetomo, Hananya Wirianta, Satriyo Nurhanudin Wibowo, Onnie Ridaliani, Djunaedi Agus Wibowo, Mohamad Romli. "The importance of understanding reservoir fluid and reservoir description in pressure transient analyses", AIP Publishing, 2023

Publication

1%

6

coek.info

Internet Source

1 %

7

www.karyailmiah.trisakti.ac.id

Internet Source

1 %

8

research.tees.ac.uk

Internet Source

1 %

Exclude quotes On

Exclude matches

< 15 words

Exclude bibliography On

Effect of nickel electroplating process time variation over aluminum on crystalplane orientation

GRADEMARK REPORT

FINAL GRADE

GENERAL COMMENTS

/0

PAGE 1

PAGE 2

PAGE 3

PAGE 4

PAGE 5

PAGE 6

PAGE 7

PAGE 8

PAGE 9